



CALCIUM SULPHATE PANEL

TOP & BOTTOM WITH GALVANIZED STEEL – EDGES SEALED WITH BLACK PVC TRIM

(Gravity Lay and/or Corner Lock style available)

Panel Structure

Pre-fabricated Calcium sulphate panel core encapsulated with 0.5mm galvanized steel on top and bottom and finished with a black PVC edge trim.

Advantage

High loading capacity with improved lateral stability with either gravity lay or corner lock style due to profiles chamfered edge finish. Non-Susceptible to humidity and moisture.

Non-combustible and 100% fully recyclable at end of life cycle.

TYPE		DS2000 (0.5/0.5)
Panel Size		600mm x 600mm x 40mm
Core Density		1500 kg /m3
Concentrated Load	N	8900
	KG	907
Impact Load	N	800
Ultimate Load	N	26700
Uniform Load	N	46000
Rolling Load /N	10 times	6668
	10,000 times	5557
Reaction to Fire		A1 / Class 0 + 1
Weight per Panel	KG	17
Pedestal and Stringer		Used in standard installations 100mm x 100mm x 2.5mm base plate M16 screw lock nut with secure engagement channels
Application		Covers all applications such as specialist, exceptionally heavy equipment rooms as well as Plant and Server Rooms. Panel ideal for HPL / Vinyl finish or carpet tile application.




PRODUCT DATASHEET DEVAR - DS2000 (CAS04)



MATCH IN ONE SQM :

- PANEL 2.78 PCS
- PEDESTAL 3.30 PCS
- SCREW 11.2 PCS

20FT GP CAPACITY: 350 M2



DEVAR HOLDINGS LIMITED

Tel: (852) 3108 2108
Fax: (852) 3108 2100

www.devargroup.com.hk
enquiries@devargroup.com.hk